

InnoStar Solutions, Inc.

PURfect Hybrid™ - 800

Elastomeric Adhesive / Sealant

Product Data Sheet

July 2023

Product Description

PURfect Hybrid - 800 is a single component, modified polyurethane that chemically reacts with moisture to deliver strong, flexible and tenacious bonds to a variety of surfaces. The product forms water-tight, weather resistant seals on joints and seams. Its flexibility allows for dissipation of stress caused by shock, vibration, or thermal movement. It is of high viscosity and exhibits excellent non-sag properties.

Features

- Strong, primerless adhesion to many metals, woods, plastics, rubbers, and masonry products
- Conforms to ASTM C-920, Type S, Grade NS, Class 50.
- USDA Accepted
- Non-sag
- Non-shrinking
- Fast skin time and final cure time
- Very low VOCs; odorless
- Non corrosive and non-staining
- Available in standard colors. Special colors upon request.
- Good retention of strength after environmental aging
- Resistant to shock, vibration and flexing
- Paintable.
- 10.1 oz cartridges; 20 oz. sausage packs; 5 gallon pails, 55 gallon drums
- Isocyanate free

Typical Physical Properties

Property	Typical Value*
Skin Time	30 minutes @ 78°F /50% RH
Tensile Strength	225 psi
Lap Shear	275 psi
Elongation	250% or more
Service Temperature	-60°F to 220°F
UV Resistance / Color Stability	Excellent
Sag	Nil
Hardness	45
VOC Content	~ 1%

*Typical values. Not for use in development of specifications

Recommendations for Use

Surface Preparation:

For reliable, repeatable and durable results, adhesives and sealants must be applied to clean, dry, sound, and frost-free surfaces. For high strength bonds, surface contaminants such as paints, oils, oxide films, mold release agents, dirt, and the like, must be completely removed. Remove old sealants or adhesives.

Application:

- Better application temperatures: 40°F - 110°F
- For best performance, sealants and adhesives should be applied to a joint at the midpoint of its designed expansion-contraction cycle
- Place nozzle into joint and fill joint entirely. Keep the nozzle in the sealant and maintain a consistent, continuous flow of sealant to minimize air entrapment.
- Tool sealant to minimize air entrapment and to assure contact with both sides of the joint.

Clean-up:

Excess adhesive should be dry-wiped from all surfaces and tools while still uncured. Mineral Spirits may be used. Cured adhesive is difficult to remove without damaging the surface it was applied to and generally must be mechanically removed.

Limitations:

- Do not apply on frost-covered surfaces.
- Not recommended for direct glazing of glass, acrylic or polycarbonate windows.
- The user should always perform relevant testing, as InnoStar Solutions does not recommend PURfect Hybrid -800 as fit for a particular use.
- Testing prior to painting is recommended.
- Shelf life of 12 months when stored at temperatures below 80°F.

Contact Information

For product prices, availability, order placement, or for additional information, contact our customer service at orderdesk@innostarsolutions.com or call (877) 250 – 1978.

PURfect Hybrid™ - 800

Elastomeric Sealant / Adhesive

Precautionary Information

Some applications may not be compatible with this product. Testing suitability for intended application before proceeding with full application is recommended. Use with adequate ventilation. In case of contact with eyes, lips, or mouth: flush thoroughly with water. Inhalation of vapor during application and cure may cause slight eye or throat irritation. If irritation persists, consult a physician. Please see SDS for additional information. **KEEP OUT OF REACH OF CHILDREN.**

Limitation of Liability

If any goods provided by InnoStar are proved to be defective, THE EXCLUSIVE REMEDY, AT InnoStar Solutions' OPTION, will be to replace the defective product or to refund the purchase price. InnoStar Solutions shall not be otherwise liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.

Disclaimer

InnoStar Solutions MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the InnoStar Solutions product is fit for a particular purpose and suitable for user's method of application. Given the variety of factors that can affect the use and performance of an InnoStar Solutions product, many of which are uniquely within the user's knowledge and control, it is essential that the user evaluate every product to determine whether it is fit for a particular purpose and suitable for the user's method of application.